

PATH TO THE FUTURE

Introducing the MSI MAG 272F X24 esports gaming monitor. This cutting-edge monitor features a 27-inch FHD display with a lightning-fast 240Hz refresh rate and a rapid 0.5ms (GtG, Min.) response time. With the MAG 272F X24, you will have the competitive advantage needed to outperform and defeat your opponents in gaming battles.



Picture and logos

SELLING POINTS

- Panel IPS Cepat - Menyediakan waktu respons 0,5 ms (GtG, Min.), mengoptimalkan warna dan kecerahan layar.
- Kecepatan Refresh 240Hz - Respons lebih cepat dengan frame yang lebih halus.
- Waktu Respons 0,5 ms (GtG, Min.) - Hilangkan gambar yang terputus-putus dan frame rate yang tersendat-sendat.
- AI Vision - Teknologi AI Vision yang baru tidak hanya dapat mengungkap detail di area gelap tetapi juga meningkatkan kecerahan keseluruhan dan menjenuhkan warna.
- Lebih Sedikit Cahaya Biru - Gunakan solusi perangkat lunak untuk mengurangi emisi cahaya di wilayah biru-ungu pada spektrum cahaya biru.



1. 5-Way Navi Key
2. AC-in
3. 2x HDMI™ 2.0b (FHD@240Hz)
4. DisplayPort 1.2a
5. Headphone-out
6. Kensington Lock

SPECIFICATION

Model	Part No	9S6-3CE51T-011
	Color	ID1/Black-Black
Display	Screen Size	27" (68.58 cm)
	Active Display Area (mm)	597.888(H) x 336.312 (V)
	Curvature	Flat
	Panel Type	Rapid IPS
	Resolution	1920x1080 (FHD)
	Pixel pitch (mm)	0.3114(H)x0.3114(V)
	Aspect Ratio	16:9
	Dynamic Refresh Rate technology	Adaptive-Sync
	Dynamic Refresh Rate Activated Range	48~240Hz
	HDR (High dynamic range)	HDR Ready
	SDR Brightness (nits)	300
	Contrast Ratio	1000:1
	DCR (Dynamic Contrast Ratio)	100000000:1
	Signal Frequency	51.9~271.1 KHz(H) / 48~240 Hz(V)
	Refresh Rate	240HZ
	Response Time (MPRT)	1ms(MPRT)
	Response Time (GTG)	0.5ms (Min.)
	View Angles	178°(H)/178°(V)
	NTSC (CIE1976 area percentage/overlap)	107%/85%
	NTSC (CIE1931 area percentage/overlap)	88%/80%
	sRGB (CIE1976 area percentage/overlap)	122%/99%
	sRGB (CIE1931 area percentage/overlap)	124%/100%
	Adobe RGB (CIE1976 area percentage/overlap)	105%/89%
	Adobe RGB (CIE1931 area percentage/overlap)	92%/83%
	DCI-P3 (CIE1976 area percentage/overlap)	97%/94%
	DCI-P3 (CIE1931 area percentage/overlap)	91%/91%
	Rec.709 (CIE1976 area percentage/overlap)	122%/99%
	Rec.709 (CIE1931 area percentage/overlap)	124%/100%
	Rec.2020 (CIE1976 area percentage/overlap)	71%/71%
	Rec.2020 (CIE1931 area percentage/overlap)	66%/66%
	Surface Treatment	Anti-glare
	Display Colors	1.07B
	Color bit	10 bits (8 bits + FRC)
I/O Ports	Headphone-out	1
	Lock type	Kensington Lock
	HDMI	2
	HDMI version	2.0b
	HDMI HDCP version	2.3
	DisplayPort	1
	DisplayPort version	1.2a
	DisplayPort HDCP version	2.3
Warranty	Warranty	36M
Power	Power Type	Internal Power Board
	Power Input	100~240V, 50/60Hz
	On-mode Power Consumption (KWh/1000h)	SDR : 21 / HDR : 30
	Annual Energy Consumption (KWh)	30.7
	Standby-mode Power Consumption (W)	0.5
	Off-mode Power Consumption (W)	0.3
	Energy Efficiency Rating	E (SDR) G (HDR)
	Power Cord Type	C13

In The Box	DisplayPort Cable	0
	HDMI Cable	1
	DVI Cable	0
	USB Type A to Type B Cable	0
	USB Type C to Type A Cable	0
	USB Type C to Type C Cable	0
	Thunderbolt Cable	0
	VGA Cable	0
	3.5mm audio Cable	0
	3.5mm combo audio Cable	0
	3.5mm Mic Cable	0
	Power Cord	1
	AC Adaptor	0
	Quick Guide	1
	Warranty Card	0
Mouse Bungee Unit	0	
Design	Adjustment (Tilt)	-5° ~ 20°
	VESA Mounting	100x100mm
Dimension & Weight (product)	Product Dimension with Stand (WxDxH) (mm)	612.64 x 249.75 x 439.98
	Product Dimension without Stand (WxDxH) (mm)	612.64 x 51.85 x 364.82
	Stand Dimension (WxDxH) (mm)	339.81 x 249.75 x 139.70
	Weight (Net kg)	3.9
	Weight Without Stand (kg)	3.5
Dimension & Weight (box)	Inside Carton Dimension (WxDxH) (cm)	66.8 x 13.1 x 44.6
	Outer Carton Dimension (WxDxH) (cm)	68.3 x 14.6 x 46.9
	Weight (Gross kg)	6.2
Barcode Info	EAN	4711377337120